

9

8

7

6

5

4

3

2

1

NOTES:
1. REFER TO MANUFACTURES SPECIFICATIONS FOR PROPER INSTALLATION AND CLINCHING PRESSURE FOR PART NUMBER 110-3132 AND 110-3181
2. -XX COLOR DESIGNATOR AS SPECIFIED IN SOP 620-8222.

REV. A 9/10/2013 PRODUCTION RELEASE 14376 RLH

REV. B 9/22/2014 REMOVE: 020-6449 (1); ADD: 020-6449-XX 14792 MMG

ITEM	PART NUMBER	Description	QTY
1	020-6430	SEAT, LATCH PIN, RB PRO	1
2	020-6441	SEAT RACK, REC	1
3	020-6449-XX	LEVER, SEAT, RB	1
4	020-6456-XX	TRACK, SEAT, MACHINED	1
5	050-2222	STICKER, SEAT POSITION, E-RB	1
6	110-3132	INSERT, CAL-12175-51	2
7	110-3172	SCREW, ISO10642, M6x16	3
8	110-3173	SCREW, M6x16, BHC, HE, ISO7380	2
9	110-3180	SCREW SHLD-12MM X 35 LG	1
10	110-3181	INSERT, M6, 610-4.2	3
11	110-3236	NUT, M6xP1.0, UNLOCK	2
12	110-3237	NUT, LOCK,M10xP1.5	1
13	110-3238	NUT, ACORN, M10	6
14	110-3256	NUT, NYLON-INSERT,M8 X 1.25	1
15	120-3248	SPACER, ARM, LEVER, E-RB	1
16	120-3256	WASHER, M10, LOCK, ISO	6
17	140-3254	SPRING, LATCH, RB, PRO BIKE	1
18	718-5259	WASHER, PA6, 20mm X 13.2mm X 1mm	3
19	720-5020	ASSY., WHEEL-BEARING, 5400	6
20	720-5073-XX	ASSY,WELD,CARRIAGE,SEAT	1

CLASS OF WORK: FINE, MEDIUM, COARSE, VERY COARSE

UNLESS OTHERWISE SPECIFIED DIMS ARE IN mm. TOLERANCES FOR MEASURE OF LENGTH ARE: 0.5 to 3, >3 to 6, >6 to 30, >30 to 120, >120 to 400, >400 to 1000, >1000 to 2000, >2000

ANGLES = ±2°

MATERIAL: SEE BOM

FINISH: SEE NOTES

VENDOR: LAND AMERICA

P/N:

THIRD ANGLE PROJECTION

CORE HEALTH & FITNESS, LLC
4400 NE 77th Ave., Suite 300
Vancouver, WA 98662

CORE PART NO: 720-5074-XX

TITLE: ASSY,SEAT TRACK,RB,8020

SCALE: 1:4

SHEET 1 OF 1

SHEET SIZE: B

DOCUMENT STATUS:

NOTICE OF PROPRIETARY INFORMATION
THIS DOCUMENT SHALL NOT BE REPRODUCED NOR SHALL THE INFORMATION CONTAINED HEREIN BE USED BY OR DISCLOSED TO OTHER EXCEPT AS EXPRESSLY AUTHORIZED BY CORE HEALTH & FITNESS, LLC.